



WINDOW PERFORMANCE RATINGS

**Windows Tested in Accordance with AAMA/WDMA/CSA 101/1.2.S/A440-2008
CSA A440.2-14 CSA & QAI Certification
(NAFS-08 + NAFS-11)**

| | | ER Rating |
|--------------------------|---|-----------|
| Contoured Casement | (Class CW-PG70-C) Air: A3, Water: PG100, Structural: PG70 | 32 - 37 |
| Contoured Awning | (Class LC-PG70-AP) Air: A3, Water: PG100, Structural: PG70 | 32 - 36 |
| Contoured Fixed Casement | (Class CW-PG70-FW) Air: Fixed, Water: PG100, Structural: PG70 | 36 - 40 |
| Contoured Picture | (Class CW-PG70-FW) Air: Fixed, Water: PG100, Structural: PG70 | 39 - 43 |
| Bevelled Casement | (Class CW-PG70-C) Air: A3, Water: PG100, Structural: PG70 | 32 - 37 |
| Bevelled Awning | (Class LC-PG55-AP) Air: A3, Water: PG100, Structural: PG55 | 32 - 36 |
| Bevelled Fixed Casement | (Class CW-PG70-FW) Air: Fixed, Water: PG100, Structural: PG70 | 36 - 40 |
| Single Slider Tilt | (Class LC-PG30-HS) Air: A3, Water: PG30, Structural: PG30 | 34 - 36 |
| Single Slider Lift Out | (Class LC-PG25-HS) Air: A2, Water: PG40, Structural: PG25 | 34 - 36 |
| Double Slider Tilt | (Class LC-PG25-HS) Air: A2, Water: PG25, Structural: PG30 | 32 - 36 |
| Double Slider Lift Out | (Class LC-PG25-HS) Air: A2, Water: PG25, Structural: PG30 | 32 - 36 |
| 3 Lite Slider Tilt | (Class LC-PG30-HS) Air: A3, Water: PG30, Structural: PG30 | 32 - 36 |
| Single Hung Tilt | (Class LC-PG35-H) Air: A2, Water: PG55, Structural: PG35 | 33 - 36 |
| Double Hung Tilt | (Class LC-PG30-H) Air: A2, Water: PG50, Structural: PG30 | 32 - 36 |

For Further Test Data Please Call 1-800-567-0141