

WINDOW PERFORMANCE RATINGS															
WINDOW TYPE	CSA-A440.00	AIR TIGHTNESS	WATER TIGHTNESS	WIND RESISTANCE	INSECT SCREEN STRENGTH	FORCED ENTRY	ENERGY STAR COMPLIANT	ENERGY STAR PROGRAM - ENERGY RATINGS							
								GLAZING							
								DUAL (LOWE SURFACE #3)				TRIPLE (LOWE SURFACE #3 & #5)			
								U-VALUE (W/(m².K))	SHGC	VISUAL LIGHT (Vt)	ENERGY RATING (ER)	U-VALUE (W/(m².K))	SHGC	VISUAL LIGHT (Vt)	ENERGY RATING (ER)
CASEMENT CONTOURED	✓	A3	B7	C5	S1	F10	✓	1.56	0.44	0.49	31	1.10	0.37	0.41	37
AWNING CONTOURED	✓	A3	B7	C5	S1	F10	✓	1.57	0.44	0.49	31	1.09	0.37	0.41	37
FIXED CASEMENT CONTOURED	✓	FIXED	B7	C5	-	F10	✓	1.64	0.45	0.48	30	1.18	0.39	0.45	37
CASEMENT BEVELLED	✓	A3	B7	C5	S1	F10	✓	1.65	0.47	0.51	31	1.16	0.41	0.47	38
AWNING BEVELLED	✓	A3	B7	C5	S1	F10	✓	1.62	0.46	0.51	31	1.12	0.39	0.43	38
FIXED CASEMENT BEVELLED	✓	FIXED	B7	C5	-	F10	✓	1.73	0.47	0.51	29	1.25	0.40	0.47	36
FIXED PICTURE	✓	FIXED	B7	C5	-	F10	✓	1.65	0.60	0.65	38	1.02	0.52	0.60	48
SINGLE SLIDER TILT	✓	A3 / FIXED	B3	C3	S1	F10	✓	1.77	0.55	0.60	33	1.20	0.48	0.55	41
DOUBLE SLIDER TILT	✓	A3	B2	C2	S1	F10	✓	1.76	0.53	0.57	32	1.21	0.46	0.53	40
SINGLE HUNG TILT	✓	A2 / FIXED	B4	C3	S1	F10	✓	1.77	0.55	0.60	32	1.20	0.48	0.55	41
DOUBLE HUNG TILT	✓	A2	B3	C2	S1	F10	✓	1.75	0.53	0.57	31	1.20	0.46	0.53	39
SINGLE SLIDER LIFT OUT	✓	A2 / FIXED	B3	C2	S1	F10	✓	1.77	0.57	0.62	33	1.18	0.49	0.57	41
DOUBLE SLIDER LIFT OUT	✓	A3	B2	C2	S1	F10	✓	1.76	0.53	0.57	32	1.21	0.46	0.53	40
3 LITE SLIDER	✓	A3 / FIXED	B3	C3	S1	F10	✓	1.77	0.55	0.60	33	1.20	0.48	0.55	41